BAX-R2UA

2U Rackmount Chassis



Features

- Up to 12" (W) x 9.6" (D) ATX compliant MB
- 6 x Internal 3.5" HDD
- Front I/O: 1 x USB 2.0
- 7 x Low profile PCIe slot (Max)
- Support PS2 ATX/1U or 2U single PSU
- 490 (D) x 428 (W) x 88.5 (H) mm
- Net weight: 5.5kg (Chassis only)



Up to 12" x 9.6" ATX compliant MB | 6 x Internal 3.5" HDD | 7 x Low profile PCIe slot (Max) | Front I/O: 1 x USB 2.0 | Support PS2 ATX/1U or 2U single PSU

Specifications

System Information	
Processor	Depend on MB
Platform Controller Hub	Depend on MB
System Memory	Depend on MB
I/O Chipset	Depend on MB
Watchdog Timer	H/W Reset, 1sec. ~ 65535sec./min.1sec. or 1min. step
H/W Status Monitor	CPU temperature monitoring Voltages monitoring CPU fan speed control
Expansion	
PCIe	1 x Full height PCIe slot (via riser card)
Front I/O	
USB	1 x USB 2.0
Power Button	1 x Power Button
Reset Button	1 x Reset Button
LED Indicator	1 x Power status, 1 x HDD, 2 x LAN
System Fan	3 x 8025

Power Requirement	
Power Supply Unit	1U/2U Single PSU PS2 ATX PSU
Mechanical & Environmental	
Operating Temp.	0°C ~ 40°C (32°F ~ 104°F)
Storage Temp.	20°C ~ 75°C (-4°F ~ 167°F)
Operating Humidity	0% ~ 90% Relative Humidity, Non-condensing
Dimension (W x L x H)	490.2 (D) x 428 (W) x 88.5 (H) mm
Weight	5.5kg (Net weight, chassis only)
Ordering Information	
Ordering Information	BCC-CASE-R2UA-01R: 2U Rackmount Chassis